

# MAKDADDY



## 3" SUPER MAK Self-Priming Pump

### Key Benefits

- | Fresh Water - Sea Water - Drilling Mud
- | Delivers improved performance, better longevity, and cost savings compared to other centrifugal pumps.
- | Parts are completely interchangeable with other pumps currently on the market.
- | Open vane impellers designed to reduce turbulence, eliminate recirculation, lower radial and thrust load while providing a smoother flow of fluid throughout the pump.
- | Recessed impeller for reduced sheering in comparison to a 250 series pump.
- | Guaranteed performance from a global company.

### SIZE - SPECIFICATIONS - OPTIONS

#### Features

- Pump series:** 3" SUPER MAK
- Pump sizes:** 3" x 3" (76 mm x 76 mm) NPT - Female
- Casing:** Gray Iron 30 Max Operating Pressure 86 psi (593 kPa)
- Semi-Open Type, Two Vane Impeller:** 3" x 3" (76 mm x 76 mm) NPT - Female
- Impeller Shaft:** Alloy Steel
- Shaft Sleeve:** Alloy Steel
- Replaceable Wear Plate:** Carbon Steel
- Removable Adjustable Cover Plate:** Gray Iron 30
- Flap Valve:** Neoprene w/Nylon and Steel Reinforcing
- Radial and Thrust Bearings:** Open Single Row Ball / Double Row Ball

# MAKDADDY



## 4" SUPER MAK Self-Priming Pump

### Key Benefits

- | Fresh Water - Sea Water - Drilling Mud
- | Delivers improved performance, better longevity, and cost savings compared to other centrifugal pumps.
- | Parts are completely interchangeable with other pumps currently on the market.
- | Open vane impellers designed to reduce turbulence, eliminate recirculation, lower radial and thrust load while providing a smoother flow of fluid throughout the pump.
- | Recessed impeller for reduced shearing in comparison to a 250 series pump.
- | Guaranteed performance from a global company.

### SIZE - SPECIFICATIONS - OPTIONS

#### Features

- Pump series:** 4" Super MAK
- Pump sizes:** 4" x 4" (101 mm x 101 mm) NPT - Female
- Casing:** Gray Iron 30 Max Operating Pressure 86 psi (593 kPa).
- Semi-Open Type, Two Vane Impeller:** Ductile Iron 65-45-12
- Handles** 3" (76,2 mm) Diameter Spherical Solids
- Impeller Shaft:** Alloy Steel
- Shaft Sleeve:** Alloy Steel
- Replaceable Wear Plate:** Carbon Steel
- Removable Adjustable Cover Plate:** Gray Iron 30
- Flap Valve:** Neoprene w/Nylon and Steel Reinforcing
- Radial and Thrust Bearings:** Open Single Row Ball